



- Note:
- Material
 - Housing: LCP UL94-V0 Color:Black.
 - Actuator: LCP UL94-V0 Color:Black.
 - Contact: Phosphor Bronze.
 - LEG: Brass.
 - Plating
 - Contact: Matte Tin Or Gold Plating Nickel Overall .
 - LEG: Matte Tin Plating Over Nickel.
 - Rating:
 - Operating Voltage: 50V AC/DC.
 - Current Rating: 0.4A AC/DC.
 - Operating Temperature: -25°C~+85°C.

PIN NO.	DIM. A	DIM. B	DIM. C
04	8.60	3.00	5.07
05	9.60	4.00	6.07
06	10.60	5.00	7.07
07	11.60	6.00	8.07
08	12.60	7.00	9.07
09	13.60	8.00	10.07
10	14.60	9.00	11.07
11	15.60	10.00	12.07
12	16.60	11.00	13.07
13	17.60	12.00	14.07
14	18.60	13.00	15.07
15	19.60	14.00	16.07
16	20.60	15.00	17.07
17	21.60	16.00	18.07
18	22.60	17.00	19.07
19	23.60	18.00	20.07
20	24.60	19.00	21.07
21	25.60	20.00	22.07
22	26.60	21.00	23.07
23	27.60	22.00	24.07
24	28.60	23.00	25.07
25	29.60	24.00	26.07
26	30.60	25.00	27.07
27	31.60	26.00	28.07
28	32.60	27.00	29.07
29	33.60	28.00	30.07
30	34.60	29.00	31.07
31	35.60	30.00	32.07
32	36.60	31.00	33.07
33	37.60	32.00	34.07

已開模PIN數如下
4, 5, 6, 8, 9, 10, 12,
18, 22, 24, 26, 28, 30

凱帛企業有限公司 KABO ENTERPRISE CO., LTD.	DESCRIPTION(內容)	DRAWN(製圖)	GENERAL TOLERANCE:(公差)		REV: A	REV	DESCRIPTION	DATE
	Pitch:1.0mm FPC SMT R/A TYPE(掀蓋式)	CHECKED(確認):	.X ±0.30 .XX ±0.15		UNIT: mm	1		2019.10.08
	PART NO: (料號) FPC-1.0-1047-xx93N	APPROVAL(核准):	SCALE(比例):	1:XX	SIZE: A4	2		
	DWG NO(圖號):				SHEET: 1/1	3		
					4			