



**NOTE:**

- 1)Electrical:
  - 1.1 Contact Resistance: 30MΩ Max
  - 1.2 Insulation Resistance:100MΩ Min
  - 1.3 Withstanding Voltage :500V DC
  - 1.4 Current rating 0.5AMP Max
  - 1.5 Temperature Rage :-55° +105°
- 2)Material:
  - 2.1 Housing: PBT+30%GF UL 94V-0
  - 2.2 Shell : Cu2680
  - 2.3 Contact :Cu2680
- 3)Finishing:
  - 3.1 Contact Plate Gold in Mating Area.  
Tin On Solder Talls.
  - 3.2 Shell: Nickel plating

PCBLayout

凱帛企業有限公司  
KABO ENTERPRISE CO., LTD.

DESCRIPTION(內容)	DRAWN(製圖)	GENERAL TOLERANCE: (公差)	REV: A	REV	DESCRIPTION	DATE
USB A DIP R/A 9PIN TYPE (藍膠)	CHECKED(確認):	.X ± .XX ±	UNIT: mm	1		2015.06.10
PART NO: (料號) USB A-2077-0991N	APPROVAL(核准):	SCALE(比例): 1:XX	SIZE: A4	2		
DWG NO(圖號):			SHEET: 1/1	3		
				4		