

項目	零件名稱	數量	材質	處理/備注
1	SHELL	1	STAINLESS	Ni: 50u"
2	Molding HOUSING	2	L.C.P	(Black)
3	GND SPRING	2	STAINLESS	Ni: 50u"
4	Insert molding 12PIN	2	L.C.P	(Black)
5	CONTACT	24	COPPER ALLOY	Contact area: gold flash, Solder tails: Tin100u", Ni: 50u"
6	PCB	1	--	--

; SPECIFICATION

MATERIAL

See drawing

STANDARD DATA

Operating temperature: -10°C ~ +60°C

Storage temperature: -20°C ~ +85°C

ELECTRICAL

Insulator resistance: 100Mohms Min.

Withstanding voltage: 100 VAC / minute

Contact resistance: initial 40mohms Max;  
after 50mohms Max.

MECHANICAL

Mating force: 5~20N

Unmating force : 8~20N

Durability: 5000 cycles Min.

凱帛企業有限公司  
KABO ENTERPRISE CO., LTD.

DESCRIPTION(內容)  
USB C TYPE R/A 24PIN  
(黑膠) 夾板式 3.1版

PART NO:  
(料 號) USB-C1010-2491N

DWG NO(圖號):


DRAWN(製圖)

CHECKED(確認):

APPROVAL(核准):

GENERAL TOLERANCE:  
(公差)

SCALE(比例):  
1:XX



REV:  
A  
UNIT:  
mm  
SIZE:  
A4  
SHEET:  
1/1

REV  
1  
2  
3  
4

DESCRIPTION

DATE

2016.07.21