



■ 技术参数 SPECIFICATIONS

- ◆ 适用线规: **AWG#32~#26**
Applicable Wire: **AWG#32~#26**
- ◆ 额定电压: **50V DC,AC(rms)**
Rated voltage: **50V DC,AC(rms)**
- ◆ 额定电流: **1A (AWG #26)**
Rated Current: **1A (AWG #26)**
- ◆ 耐压值: **500V AC/minute**
Withstand voltage: **500V AC/min.**
- ◆ 工作温度: **-25°C ~ +85°C**
Working Temp : **-25°C ~ +85°C**
- ◆ 绝缘电阻: $\geq 500 \text{ M}\Omega$
Insulation resistance: $\geq 500 \text{ M}\Omega$
- ◆ 接触电阻: $\leq 20 \text{ m}\Omega$
Contact resistance: $\leq 20 \text{ m}\Omega$

■ 材料 MATERIAL

- ◆ 绝缘体: **Nylon9T, UL-94-V0**
Insulator: **Nylon9T, UL-94-V0**
- ◆ 接触针: **黄铜**
Contact PIN: **Brass**
- ◆ 焊片: **磷铜**
Solder tab: **Phosphor bronze**

| | 2A | 3A | 4A | 5A | 6A | 7A | 8A | 9A | 10A |
|--------------|-------------|-------------|-------------|--------------|--------------|--------------|--------------|--------------|--------------|
| DIM.A | 1.50 | 3.00 | 4.50 | 6.00 | 7.50 | 9.00 | 10.50 | 12.00 | 13.50 |
| DIM.B | 6.00 | 7.50 | 9.00 | 10.50 | 12.00 | 13.50 | 15.00 | 16.50 | 18.00 |

| | | |
|----------------------------------|----------|---------|
| 凱帛企業有限公司 KABO ENTERPRISE LTD. | | |
| Name | | |
| Pitch: 1.5 WAFER SMT R/A TYPE | | |
| Drawing No. | | |
| WF-1.5-1008-xx93N | | |
| DR | CHK | APPD |
| General Tolerances : | | Unit : |
| XX ±0.40 | X ±0.30 | mm |
| X ±0.25 | X' ± 2' | |
| .XX ±0.15 | .X' ± 1' | |
| | | Scale : |
| | | ROM |