



NOTES

1. MATERIAL & FLASH/PLATED
 - 1.1 HOUSING: HIGH TEMP. THERMOPLASTIC
[UL 94V-0]; COLOR: BLACK
 - 1.2 PROBE: COPPER ALLOY
.PLATING: 5u" GOLD ON CONTACT AREA
 - 1.3 SPRING: STAINLESS SERIES
.PLATING: NONE PLATING
2. PRODUCT SPECIFICATION
 - 2.1 DISPLACEMENT: 1.10 mm.MIN.
 - 2.2 CONTACT RESISTANCE: 50MILLIOHMS MAX.
 - 2.3 NORMAL FORCE: PRE-LOAD=0gf MIN.
FULL-LOAD=160±30gf
NOTES: FULL-LOAD DISPLACEMENT: 1.5±0.1mm
 - 2.4 DURABILITY: 10,000CYCLE [SPRING FORCE 20% LOSS]
NOTES: REDUCTION OF ORIGINAL FORCE 20% LOSS.
4. PACKAGE: TAPE REEL
5. PC BOARD THICKNESS: 1.0mm REF.

凱帛企業有限公司
KABO ENTERPRISE CO., LTD.

DESCRIPTION(內容):
BATTERY CONNECTOR SMT TYPE 1 PIN

PART NO:
(料 號) Battery-1005-0101N

DWG NO(圖號):

DRAWN(製圖):

CHECKED(確認):

APPROVAL(核准):

GENERAL TOLERANCE:
(公差)

.X 0.30
.XX 0.20
.XXX 0.10

SCALE(比例):
1:XX



REV:
A/1

UNIT:
mm

SIZE:
A4

SHEET:
1/1

REV

1

2

3

4

DESCRIPTION

△ 圖面中有此符號表示重點尺寸

DATE

2006.08.08