



# Specifications :

1. Electrical
  - Rated Voltage: 600V AC, DC
  - Rated Current: 1.0A
  - Withstand Voltage: 1800V AC/minute
  - Contact Resistance: 20mΩ (MAX.)
  - Insulation Resistance: 1000MΩ (MIN.)
  - Temperature Range: -25°C~+85°C
2. Material      Circuits: 02~05
  - Base : PA6T/PA9T; UL 94V-0
  - Contact : Phosphor bronze
  - Hold down : Brass
3. Finish
  - Contact : Tin over Nickel
  - Hold down : Tin over Nickel

### Dimensional & Ordering Information:

Cir- cuits	Pitch	Part NO.	Dimension mm			
			A	B	C	D
02	4	Wafer-4.0-1001-0293N	4.0	10.0	6.76	7.86
	8	Wafer-8.0-1001-0293N	8.0	14.0	10.76	11.86
	12	Wafer-12.0-1001-0293N	12.0	18.0	14.76	15.86
	16	Wafer-16.0-1001-0293N	16.0	22.0	18.76	19.86
03	4	Wafer-4.0-1001-0393N	8.0	14.0	10.76	11.86
	4/8	Wafer-4.0/8.0-1001-0393N	12.0	18.0	14.76	15.86
04	4	Wafer-4.0-1001-0493N	12.0	18.0	14.76	15.86
05	4	Wafer-4.0-1001-0593N	16.0	22.0	18.76	19.86

凱帛企業有限公司  
KABO ENTERPRISE CO., LTD.

DESCRIPTION(內容):  
WIRE TO BOARD SMT R/A TYPE

PART NO:  
(料 號) Wafer-xx-1001-xx93N

DWG NO(圖號):

DRAWN(製圖):

CHECKED(確認):

APPROVAL(核准):

GENERAL TOLERANCE:  
(公差)

.X ±0.25  
.XX ±0.13  
.XXX±0.08

SCALE(比例):  
1:XX

REV:  
A

UNIT:  
mm

SIZE:  
A4

SHEET:  
1/1

REV	DESCRIPTION	DATE
1		2006.06.15
2		
3		
4		