



RECOMMENDED P.C. BOARD PATTERN DIM.

## Specifications:

### Electrical

Rated Voltage: 50V AC, DC

Rated Current: 1A

Withstand Voltage: 500V AC/minute

Contact Resistance: 20mΩ (MAX.)

Insulation Resistance: 100MΩ (MIX.)

Temperature Range: -25°~+85°C

### Material and Finish:

Circuits: 02~16, 20

Material: High Temperature plastic UL94V-0

### Dimensional & Ordering Information:

Cir- cuits	Dimension mm			REEL /PCS
	A	B	C	
02	1.0	4.0	2.5	1,000
03	2.0	5.0	3.5	1,000
04	3.0	6.0	4.5	1,000
05	4.0	7.0	5.5	1,000
06	5.0	8.0	6.5	1,000
07	6.0	9.0	7.5	1,000
08	7.0	10.0	8.5	1,000
09	8.0	11.0	9.5	1,000
10	9.0	12.0	10.5	1,000
11	10.0	13.0	11.5	1,000
12	11.0	14.0	12.5	1,000
13	12.0	15.0	13.5	1,000
14	13.0	16.0	14.5	1,000
15	14.0	17.0	15.5	1,000
16	15.0	18.0	16.5	1,000
20	19.0	22.0	20.5	1,000

PRODUCT NO.	REVISION	DATE	DESCRIPTION	UNIT: mm	凱帛企業有限公司 KABO ENTERPRISE CO., LTD.	DRAWING	CHECKED	APPROVAL
WAFER	A	2003.12.26	NEW DWING	TOLERANCE : .000 :±0.08				
	B	2004.01.28	ADD Circuits	.00 :±0.13				
PART NO	Wafer-1.0-1002-xx03N			.0 :±0.25				