



**SPECIFICATION:**

PITCH BETWEEN POLES : 1.25mm

CURRENT RATING : 1A AC/DC

VOLTAGE RATING : 100V AC/DC

CONTACT RESISTANCE : 20mΩ(max.)

INSULATION RESISTANCE : 500MΩMIN

WITHSTAND VOLTAGE : 500V AC/MINUTE

TEMPERATURE RANGE : -25° C TO +85° C

**FEATURES:**

AVAILABLE NUMBER OF CIRCUITS : 2x5 TO 2x20 DUAL ROW

MATERIAL : NYLON 6T UL 94V-0

CONTACT : 0.35mm(.014") SQUARE PIN,  
BRASS , TIN PLATED

Poles	Part No	DIM:(mm)	
		A	B
10	Wafer-1.25-1003-1003	5.00	8.09
20	Wafer-1.25-1003-2003	11.25	14.34
30	Wafer-1.25-1003-3003	17.50	20.59
40	Wafer-1.25-1003-4003	23.75	26.84

凱鼎企業有限公司 KABO ENTERPRISE LTD.		
Name Pitch1.25mm WIRE TO BOARD SMT V/T TYPE		
Drawing No. Wafer-1.25-1003-xx03		
DR <i>Tom</i>	CHK <i>[Signature]</i>	APPD <i>May</i>
General Tolerances x.xx±0.5 x.xx±0.8	Unit mm	Date ROK