



RECOMMENDED P.C.BOARD HOLE DIMM.

Specifications:

Electrical

Rated Voltage: 100V AC, DC

Rated Current: 1A

Withstand Voltage: 250V AC/minute

Contact Resistance: 20mΩ (MAX.)

Insulation Resistance: 100MΩ (MIN.)

Temperature Range: -25°~+85°C

Material and Finish:

Circuits: 02-15

Material: NYLON46 UL94V-0

Dimensional & Ordering Information:

Cir- cuits	Part No	Dimension mm		
		A	B	C
02	Wafer-1.25-1007-0293	1.25	4.25	7.45
03	Wafer-1.25-1007-0393	2.50	5.50	8.70
04	Wafer-1.25-1007-0493	3.75	6.75	9.95
05	Wafer-1.25-1007-0593	5.00	8.00	11.20
06	Wafer-1.25-1007-0693	6.25	9.25	12.45
07	Wafer-1.25-1007-0793	7.50	10.50	13.70
08	Wafer-1.25-1007-0893	8.75	11.75	14.95
09	Wafer-1.25-1007-0993	10.00	13.00	16.20
10	Wafer-1.25-1007-1093	11.25	14.25	17.45
11	Wafer-1.25-1007-1193	12.50	15.50	18.70
12	Wafer-1.25-1007-1293	13.75	16.75	19.95
13	Wafer-1.25-1007-1393	15.00	18.00	21.20
14	Wafer-1.25-1007-1493	16.25	19.25	22.45
15	Wafer-1.25-1007-1593	17.50	20.50	23.70

凱帛企業有限公司
KABO ENTERPRISE CO., LTD.

DESCRIPTION(內容)

Pitch1.25mm WIRE TO BOARD

SMT R/A TYPE

PART NO:
(料號) Wafer-1.25-1007-xx93

DWG NO(圖號):

DRAWN(製圖)

CHECKED(確認):

APPROVAL(核准):

GENERAL TOLERANCE:
(公差)

.X ±0.30
.XX ±0.20
.XXX±0.10

SCALE(比例):
1:XX



REV:
A

UNIT:
mm

SIZE:
A4

SHEET:
1/1

REV

1

2

3

4

DESCRIPTION

DATE