



RECOMMENDED P.C. BOARD HOLE DIMM.

## Specifications:

Electrical

Rated Voltage: 150V AC, DC

Rated Current: 1A

Withstand Voltage: 500V AC/minute

Contact Resistance: 30mΩ (MAX.)

Insulation Resistance: 500MΩ (MIN.)

Temperature Range: -35°~+85°

Material and Finish:

Circuits: 20, 25, 30

Material: PA6T UL 94V-0

## Dimensional & Ordering Information:

| Cir-<br>cuits | Part No              | Dimension mm |       |       | TUBE<br>PCS | REEL<br>PCS |
|---------------|----------------------|--------------|-------|-------|-------------|-------------|
|               |                      | A            | B     | C     |             |             |
| 20            | Wafer-1.25-1012-2093 | 23.75        | 30.00 | 29.00 | 18          | 1,500       |
| 25            | Wafer-1.25-1012-2593 | 30.00        | 36.20 | 35.20 | 15          | 1,500       |
| 30            | Wafer-1.25-1012-3093 | 36.25        | 42.45 | 41.45 | 13          | 1,500       |

|                                 |                  |           |  |                                   |
|---------------------------------|------------------|-----------|--|-----------------------------------|
| 比例(SCALE)                       | FREE             | 繪圖(DRAW)  | 凱島企業有限公司<br>KABO ENTERPRISE CO. LTD            |                                   |
| 單位(UNIT)                        | mm               | 審核(CHECK) |  |                                   |
| 一般公差 (TOLERANCE)                | 承認(AP' E)        | 圖名(NAME): | Pitch1.25mm Post<br>WIRE TO BOARD SMT R/A TYPE |                                   |
| .0=±0.35<br>.00=±0.2<br>ANG=±5° | 投影法<br>PROJECNON | 第三角       |  | 料號(PART NO.) Wafer-1.25-1012-xx93 |