



Specifications

Electrical

Voltage Rating: 100V(AC)
 Current Rating: 2A
 Contact Resistance: 20m Ω max.
 Dielectric Withstandeing Voltage: 800V AC/1min.
 Insulation Resistance: 1000M Ω min.

Material

Circuits: 2~16
 Insulator: Nylon 66 UL 94V-0
 Color: White or Natural
 Contact: Brass 0.50mm(0.20") Square Wire Pins
 Plating: Tin or Gold Plated
 Temperature Range: -25° C~+85° C
 Applicable PC Board Thickness: 0.8 to 1.6mm

Poles	Dimension (in.)	
	A	B
2	2.0(0.079)	6.1(0.240)
3	4.0(0.157)	8.1(0.318)
4	6.0(0.236)	10.1(0.397)
5	8.0(0.315)	12.1(0.476)
6	10.0(0.394)	14.1(0.555)
7	12.0(0.472)	16.1(0.634)
8	14.0(0.551)	18.1(0.713)
9	16.0(0.630)	20.1(0.791)
10	18.0(0.709)	22.1(0.870)
11	20.0(0.787)	24.1(0.949)
12	22.0(0.886)	26.1(1.028)
13	24.0(0.945)	28.1(1.106)
14	26.0(1.024)	30.1(1.185)
15	28.0(1.102)	32.1(1.263)
16	30.0(1.181)	34.1(1.343)

凱帛企業有限公司 KABO ENTERPRISE LTD.		
Name		
Pitch2.0mm Wafer DIP V/T Type		
Drawing No.		
Wafer-2.0-2001-xx01		
DR	CHK	APPD
General Tolerances : x.xx±0.1 x.x±0.5	Unit : mm	Scale : ROM