



RECOMMENDED P.C. BOARD HOLE DIMM.

所有材料為
"環保材料"
2006. 6. 29
RoHS

Specifications

Current Rating: 5A AC, DC
 Voltage Rating: 250V AC Maximum
 Operating Temp: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Terminal Material: Brass/Tin-plated
 Material: Nylon 66, UL94V-0

Poles	Dimension mm (in)		Note.
	A	B	
2	3.96 (0.156)	7.92 (0.312)	
3	7.92 (0.312)	11.92 (0.469)	
4	11.88 (0.468)	15.84 (0.624)	
5	15.84 (0.624)	19.84 (0.781)	
6	19.80 (0.780)	23.80 (0.937)	
7	23.76 (0.935)	27.88 (1.098)	
8	27.72 (1.074)	31.74 (1.250)	
9	31.68 (1.247)	35.86 (1.412)	
10	35.64 (1.403)	39.90 (1.571)	
11	39.60 (1.559)	43.84 (1.726)	
12	43.56 (1.715)	47.92 (1.887)	
13	47.52 (1.871)	51.72 (2.036)	
14	51.48 (2.027)	55.92 (2.202)	
15	55.44 (2.182)	59.88 (2.357)	

※備註：15Pin為特殊Pin數，下單時須有M.O.Q

凱帛企業有限公司 KABO ENTERPRISE LTD.		
Name Pitch3.96mm WAFER DIP V/T TYPE		
Drawing No. WAFER-3.96-2001-xx01N		
DR	CHK	APPD
General Tolerances : x.xx±0.25 x.x±0.30	Unit : mm	Scale : ROM